



Certificate number: 2102710 (2)

Issued 21/12/2023

Expires 01/02/2026

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Henco Industries NV.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Henco Industries NV
Toekomstlaan 27 B-2200 HERENTALS
Belgium



KUKreg4

Product Certificate

Appendix to Certificate number: 2102710

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Henco range of plastic PVDF push fit (Vision) fittings, incorporating EPDM rubber 'O'-rings, nickel plated brass compression (Schroef) fittings and press fit (Brass and PVDF) fittings, incorporating EPDM rubber 'O'-rings, all for use with Henco standard multi-layer pipe (PE-xc/AL/PE-xc) only. Crimping for press fit models is achieved via specialised crimping tool. For above ground use only. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) Vision (push fit): 16 - 26mm. Schroef (compression): 16 - 26mm. Brass (press fit): 14mm - 32mm. PVDF (press fit) 14mm - 75mm. Henco standard multi-layer pipe (PE-xc/AL/PE-xc): 14mm - 75mm.</p>
<p>SIZE: Vision (push fit): 16 - 26mm. Schroef (compression): 16 - 26mm. Brass (press fit): 14mm - 32mm. PVDF (press fit) 14mm - 75mm. Henco standard multi-layer pipe (PE-xc/AL/PE-xc): 14mm - 75mm.</p>
<p>SCOPE: Supplier recommended maximum working pressure 10 Bar & maximum operating temperature 95°C Hygienic Purposes: Non-metallic materials suitable for continuous use up to 70°C Above ground use only.</p>
<p>MARKING Pipe: HENCO, trade mark, origin of manufacturer, contact details, PE- XC/AL, size, code number, max pressure and temp, KIWA, ISO number and product information on pipe. PVDF (press fit) fittings: Size and PVDF on body. Henco on press connection. Brass (press fit) fittings: HN, Henco logo and size on body. Schroef (compression) and Vision (push fit) fittings: Henco and size on body.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES Opacity. All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes