



Certificate number: 2102711 (2)

Issued 21/12/2023 Expires 01/02/2026

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a) Model number(s) – see Appendix

Henco Industries NV.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

DATE

David Jay, Business Unit Manager – Authorised Signatory Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply. See https://www.kiwa.com/gb/en/about-kiwa/water-products/ or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec

(A Trading Division of Kiwa Ltd) 26A Rassau Industrial Estate Ebbw Vale Gwent NP23 5SD

United Kingdom

T +44 (0)1495 308185

uk.water@kiwa.com

www.kiwa.co.uk

Certificate Issued to:

Henco Industries NV Toekomstlaan 27 B-2200 HERENTALS Belgium





Product Certificate



Appendix to Certificate number: 2102711

The following products belong to this certificate

PRODUCT DESCRIPTION

Henco range of nickel plated brass fittings and press fit (Brass and PVDF) fittings, incorporating EPDM rubber 'O'-rings, all for use with Henco RIXC Multilayer pipe (PE–xc/AL/PE-xc) only. Crimping for press fit models is achieved via specialised crimping tool. For above ground use only.

ATS3 - Without Production Surveillance

MODEL(S)

Henco Press PVDF fitting (PKW): 16, 20, 26 & 32mm.

Henco brass press fitting (P): 16, 20 & 26mm Henco Schroef fitting (EK):12mm compression.

Henco RIXC Multilayer pipe PEXc/AL/PEXc: 12, 16, 20, 26 & 32mm.

SIZE:

See model.

SCOPE:

Supplier recommended maximum working pressure 10 Bar & maximum operating temperature 95°C.

Hygienic purposes: Non-metallic materials suitable for continuous use up to 70°C.

Above ground use only.

MARKING

Fittings Henco Press PVDF fitting (PKW) + Press Brass (P): Henco and size on crimped connector. Henco, size, PKW and date of manufacture (clock format) on body. Henco Schroef (EK) fittings: HN (Stands for Henco) cast on nut. Pipe: Henco, PEXc/AL/PEXc, size, class, made in Belgium and other technical information printed on body.

MATERIALS

Non-Metallic materials assessed (BS6920) to point of discharge.

BACKFLOW PROTECTION NOTES

N/A.

ADDITIONAL NOTES

Opacity.

Opacity cannot be guaranteed on the PVDF range of fittings.

Extra Notes